

Serial No. 10/658,769
Reply to Office Action

Docket No. IMED-0010-US

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A ventilation interface ~~adapted to be inserted into a nares of a user to secure the interface,~~ comprising:

a cannula with at least one nasal insert and at least one exhaust port; the cannula forming a first portion of an input gas flow passage to supply the ventilation gas to the user;

the first portion of an input gas flow passage is substantially axially aligned with the at least one nasal insert;

~~the nasal insert adapted to be inserted into a first naris of the nares of the user,~~
the at least one nasal insert forming second and third portions of the input gas flow passage from the cannula to a distal end of the nasal insert; and

a seal portion adapted to engage at least a portion of the nares, the seal portion being provided on the distal end of the at least one nasal insert;

~~wherein the first, second and third portions of the input gas flow passage are disposed at an obtuse angle to one another.~~

2. (currently amended) The ventilation interface according to claim 1, wherein the wherein the first, second and third portions of the input gas flow passage are disposed at an obtuse angle to one another. ~~obtuse angle is between about 110° and about 170°.~~

Serial No. 10/658,769
Reply to Office Action

Docket No. IMED-0010-US

3. (original) The ventilation interface according to claim 2, wherein the obtuse angle is about 135°.
4. (original) The ventilation interface according to claim 1, wherein the proximal end of the nasal insert forms a second portion of the input gas flow passage having a substantially oval cross section.
5. (original) The ventilation interface according to claim 4, wherein a distal end of the nasal insert forms a third portion of the input gas flow passage having a substantially oval cross section.
6. (original) The ventilation interface according to claim 5, wherein the third portion of the input gas flow passage has a circumference that is less than a circumference of the second portion of the input gas flow passage.
7. (original) The ventilation interface according to claim 6, wherein the seal portion forms a third portion of the input gas flow passage having a substantially oval cross section.
8. (original) The ventilation interface according to claim 7, wherein the distal end of the nasal insert includes a first exterior portion having a substantially oval cross section.

Serial No. 10/658,769
Reply to Office Action

Docket No. IMED-0010-US

9. (original) The ventilation interface according to claim 8, wherein the portion of the nasal insert proximal the cannula includes a second exterior portion having a substantially oval cross section.
10. (original) The ventilation interface according to claim 9, wherein the first exterior portion has a circumference that is less than a circumference of the second exterior portion.
11. (original) The ventilation interface according to claim 10, wherein the seal portion includes a third exterior portion having at least one of a substantially oval cross section or a round cross section.
12. (original) The ventilation interface according to claim 11, wherein the third exterior portion has a circumference that is larger than the circumference of the second exterior portion.
13. (original) The ventilation interface according to claim 11, wherein the third exterior portion has a circumference that is substantially equal to the circumference of the second exterior portion.
14. (original) The ventilation interface according to claim 1, further comprising:
a gas output forming a portion of an output gas flow passage from the nasal insert to an exterior of the ventilation interface to channel a gas expired by the user.

Serial No. 10/658,769
Reply to Office Action

Docket No. IMED-0010-US

15. (original) The ventilation interface according to claim 14, wherein the second portion of the input gas flow passage formed by the nasal insert is about parallel with the portion of the output gas flow passage.

16. (original) The ventilation interface according to claim 15, wherein the second portion of the input gas flow passage and the portion of the output gas flow passage are configured to provide laminar flow therebetween.

17. (original) The ventilation interface according to claim 16, wherein a distal end of the gas output forms a first portion of the output gas flow passage having a substantially circular cross section.

18. (original) The ventilation interface according to claim 17, wherein a portion of the gas output proximal the cannula forms a second portion of the output gas flow passage having a substantially circular cross section.

19. (original) The ventilation interface according to claim 18, wherein the first portion of the output gas flow passage has a circumference that is less than a circumference of the second portion of the output gas flow passage.

20. (original) The ventilation interface according to claim 1, wherein at least one of the nasal insert and the seal portion is sufficiently flexible to be expanded by a positive pressure provided by the ventilation gas.

Serial No. 10/658,769
Reply to Office Action

Docket No. IMED-0010-US

21. (original) The ventilation interface according to claim 1, wherein at least one of the nasal insert and the seal portion forms a seal with the nares of the user by at least one of deformation of at least one of the nasal insert, the nares of the user, the seal portion or a headgear.

22. (original) The ventilation interface according to claim 1, wherein at least one of the nasal insert and the seal portion forms a seal with the nares of the user by friction between the nares of the user and at least one of the nasal insert, the seal portion or a headgear.

23. (original) The ventilation interface according to Claim 1, wherein at least one of the nasal inserts and the seal portion form a seal with at least one naris of the user by a resiliency of at least one of said seal portion and said nares of the user and a headgear.

24. (withdrawn)

25. (withdrawn)

26. (withdrawn)

27. (withdrawn)

28. (currently amended) A ventilation interface adapted to be inserted into a nares of a user to secure the interface, comprising:

Serial No. 10/658,769
Reply to Office Action

Docket No. IMED-0010-US

means for forming a first portion of an input gas flow passage being substantially axially aligned with at least one nasal insert ~~from a ventilation gas supply source;~~

means for forming a second portion of the input gas flow passage from the means for forming the first portion to a first naris of the nares of the user; and

means for engaging a portion of the nares provided on the means for forming a second portion of the input gas flow passage;

~~wherein the first and second portions of the input gas flow passage are disposed at an obtuse angle to one another.~~

29. (withdrawn)

30. (currently amended) A ventilation or CPAP interface system, comprising:

a cannula, nasal inserts, seal portions and exhaust ports;

feed tubes and a Y-connector;

a tubing connector;

head gear;

the cannula is adapted to be connected to ~~a source of ventilation gas~~ via the feed tubes and Y-connector, the cannula forming a first portion of an input gas flow passage;

the first portion of an input gas flow passage being substantially axially aligned with the at least one nasal insert;

~~the nasal inserts are adapted to be inserted into the nares of the user,~~ the nasal inserts form a second portion of the input gas flow passage from the cannula to a distal end of the nasal inserts; and

Serial No. 10/658,769
Reply to Office Action

Docket No. IMED-0010-US

a seal portion adapted to engage at least a portion of the nares, the seal portion provided adjacent a distal end of the nasal insert[:].

~~wherein the first and second portions of the input gas flow passage are disposed at an obtuse angle to one another.~~

31. (original) The ventilation interface according to claim 1 wherein the seal portion is configured to receive a skirt to prevent leakage.

32. (new) The ventilation interface as in claim 1, wherein the first portion of an input gas flow passage being oriented in a downward fashion is connected to a feed tube.

33. (new) The ventilation interface as claim 32, wherein the feed tube has a y-connector.